

PRECISION INSTRUMENT COMPANY

BIMETAL THERMOMETER ADJUSTABLE ANGLE TYPE 'B5Ax'



STANDARD FEATURES

- All Stainless Construction
- With Glass Lens
- Anti-Parallax Dial
- Vibration Resistant (Reduced Needle Flutter)
- Fast Response To Temperature Change
- Hermetically Sealed (Moisture Proof)
- +/- 1 % Full Scale Accuracy
- Stem Welded To Connection



PART NUMBER	STEM LENGTH*
B5A2	2 1/2"
B5A4	4"
B5A6	6"
B5A9	9"
B5A12	12"
B5A15	15"
B5A18	18"
B5A24	24"

STANDARD RANGES*	
CODE	RANGE
AA	-40/120 F & C
BB	-40/160 F & C
EE	0/150 F & C
GG	0/200 F & C
JJ	20/240 F & C
II	0/250 F & C
MM	50/300 F & C
PP	50/400 F & C
RR	50/550 F & C
SS	150/750 F & C
TT	200/1000 F & C



***NOTE:**

- 1.) OTHER RANGES, STEM LENGTHS AND CONFIGURATIONS ARE AVAILABLE UPON REQUEST.
- 2.) THERMOWELLS OF ALL TYPES AND MATERIALS OF CONSTRUCTION AVAILABLE ALSO
- 3.) PLEASE CALL WITH ANY INQUIRIES.

	A	B	C	D	E
IN.	5.13"	STEM LENGTH	1/4"	.67"	3.3"
MM	130.39	STEM LENGTH	6.45	16.95	83.87